



- Measuring range from 0 to 400 bar abs.
- Measuring accuracy starting with $\pm 0.1\%$ F.S.
- Large selection of pressure sensors
- Automatic sensor recognition
- Absolute pressure measurement, Relative pressure measurement
- Serial interface, minimum/maximum memory, hold function, real-time clock, logger function
- Differential pressure measurement
- Robust housing, IP 65, front



KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, FRANCE, GERMANY, GREAT BRITAIN, INDIA, IRAN, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, SINGAPORE, SLOVAKIA, SPAIN, SWITZERLAND, THAILAND, USA, VENEZUELA, VIETNAM

KOBOLD Messring GmbH
 Nordring 22-24
 D-65719 Hofheim/Ts.
 ☎ +49(0)6192 299-0
 Fax +49(0)6192 23398
 E-Mail: info.de@kobold.de
 Internet: www.kobold.com

Model:
 HND-P



Nearly all measuring tasks for the determination of pressure can be performed with the HND-P series KOBOLD hand-held pressure measuring devices. Various housing designs make it possible to find the right housing with the appropriate characteristic for every application. In addition to the large selection of external pressure sensors up to max. 400 bar absolute, measuring devices with integrated sensors in the millibar range are also available.

In the following table, all KOBOLD hand-held pressure measuring devices are listed with their respective equipment characteristics to ensure fast classification. Further technical data and additional information regarding the individual housings can be found in the subsequent pages.

Characteristics of the hand-held measuring devices of the HND-P... series

		HND-P105	HND-P210/215	HND-P121/231	HND-P123/233	HND-P126/236	HND-P127	HND-P129/239
Pressure measurement	external	X	X	–	–	–	–	–
	internal	–	–	X	X	X	X	X
Measuring range		depending upon the sensor		-1,00... 25.00 mbar	-10,0... 350.0 mbar	-100... 2000 mbar	-10,0... 420.0 mbar	0... 1300 mbar
Accuracy		±0.1% F.S. ±1 Digit*	±0.1% F.S. ±1 Digit*	Start. with ±0.3% F.S.	Start. with ±0.2% F.S.	Start. with ±0.2% F.S.	Start. with ±0.1% F.S.	Start. with ±0.2% F.S.
Display (LCD)		2 x 4-digit	2 x 4-digit	2 x 4-digit	2 x 4-digit	2 x 4-digit	2 x 4-digit	2 x 4-digit
Output	0-1 Volt	–	–	–	–	–	–	–
	Interface	X	X	X	X	X	X	X
Connection		6 four-pin Mini-DIN plug		2 hose connection nipples made of metal				1x hose connection nipples
Minimum/maximum value memory		X	X	X	X	X	X	X
Minimum/maximum alarm		–	X	only HND-P231	only HND-P233	only HND-P236	–	only HND-P239
Alarm		–	X	only HND-P231	only HND-P233	only HND-P236	–	only HND-P239
Auto-off funktion		X	X	X	X	X	X	X
Hold function		X	X	X	X	X	X	X
Zero point offset entry		X	X	X	X	X	X	X
Differential measurement		–	only HND-P215	X	X	X	X	–
Logger function		–	X	only HND-P231	only HND-P233	only HND-P236	–	only HND-P239
Real-time clock		–	X	only HND-P231	only HND-P233	only HND-P236	–	only HND-P239
Power supply	Battery	X	X	X	X	X	X	X
	External	X	X	X	X	X	X	X

*Measurement device precision, without consideration for the precision of the respective sensor



- Connection for external sensor
- 2 connections with HND-P215
- display of 2 measuring points
- differential pressure measurement
- Serial interface
- Logger function with HND-P210/215
- Relative pressure sensors

Description

The KOBOLD hand-held pressure measuring devices HND-P105/210/215 are highly precise, compact pressure measuring devices that can be used universally. In conjunction with the appropriate external pressure sensors, precise measurement results over the entire measuring range can be achieved. Various pressure sensors are available for a multitude of measuring tasks and special applications. The respective measurement task determines which combination is selected. Naturally, these first-rate KOBOLD-measuring units can display more than just pressure. All devices in this series allow for minimum/maximum value memory, hold function, automatic self-shut-off, or zero point offset entry for all connected pressure sensors, for example. The HND-P210/215 types also have a logger function, a peak value memory, or a minimum/maximum alarm. A special characteristic of the type HNDP215 is the possibility of connecting two external pressure sensors.

Areas of application

- Chemical, pharmaceutical, food industry
- Machine and apparatus construction
- Piping and container construction

Technical Data

(The data listed refers to the measuring unit without consideration for the respective sensors)

Measurement input: for pressure sensor HND-PS
 Measuring range: depending upon the pressure sensor
 Accuracy: ± 0.1% F.S. ± 1 Digit (at nominal temperature 25 °C)
 Resolution: depending upon the sensor
 Display range: -1999 ... +9999
 Display: 2 x 4-digit LCD-displays
 Operating temperat.: -25 to +50 °C
 Storage temperat.: -25 to +70 °C
 Storage humidity: 0 to 95 % r.H. (non-condensing)
 Probe connection: 6-pin shielded Mini-DIN plug, autom. sensor recognition, and measuring range adjustment
 Output: serial interface (via 3-pin jack, transformer on RS232 or USB optional)
 0-1 V (freely scalable) only for HND-P215

Technical Data (continued)

Power supply: 9 V-monobloc battery (included in the scope of delivery) external 10,5 - 12 V_{DC} via jack
 Current consumption: approx. 3 mA
 Housing material: made of impact-resistant ABS-K
 Degree of protection: IP 65, front
 Dimensions: 142 x 71 x 26 mm (H x W x D)
 Weigh: approx. 150 g

Scope of functions

Minimum/maximum value memory
 Hold function: »freezing« of the current value
 Automatic-off function: 1...120 min (can be deactivated)
 Zero point adjustment for connected sensor
 Tare function: display-, minimum/maximum values are set to zero
 Additional functions with type HND-P210/215:
 Minimum/maximum alarm can be deactivated
 Alarm (3 alarm settings)
 Off: Alarm function inactive
 On: Alarm notification via display, internal horn and serial interface
 No Sound: Alarm notification only via display and interface

Averaging

Peak value memory unfiltered pressure peaks ≥ 10 msec
 Adjustable measuring cycle:
 »slow« 4 measurements/sec
 »fast« ≥ 100 measurements/sec (filtered)
 »peak-detect« ≥ 100 measurements/sec

Power saving mode for measuring cycle »slow«
 Real-time clock: current time with date and year

Logger functions:

Manual: 99 datasets
 Cyclic: 9999 datasets (only HND-P210)
 3600 datasets (only HND-P215)
 Adjustable cycle time: 1 sec...1 h

2 pressure sensor connections (only HND-P215)

Order data

Order-no.	Housing design
HND-P 105	1 x pressure sensor input, standard
HND-P 210	1 x pressure sensor input with additional functions (see techn. data)
HND-P 215	2 x pressure sensor inputs with additional functions (see techn. data)

Suitable probe and accessories see pages 38 and 42

Pressure sensors for HND-P 105, HND-P 210 und HND-P 215

Measurement principle: piezo-resistive
 Cable connection: 1 m PVC, screened

Measuring range	Accuracy	Resolution	Overload	Connection	Order-no.
-1.999...2.500 mbar	$\pm 0.2\%$ F.S. / $\pm 1.0\%$ F.S.*	0.001 mbar	max. 200 mbar	Nylon spigot for hose 6 x 1 mm 	HND-PS01**
-19.99...25 mbar	$\pm 0.2\%$ F.S. / $\pm 0.5\%$ F.S.*	0.01 mbar	max. 300 mbar		HND-PS02**
-199.9...350.0 mbar	$\pm 0.2\%$ F.S. / $\pm 0.4\%$ F.S.*	0.1 mbar	max. 1 bar		HND-PS03**
-1000...2000 mbar		1 mbar	max. 4 bar		HND-PS04**
-1...10 bar		10 mbar	max. 10.34 bar		HND-PS05**
0...1300 mbar abs.		1 mbar	max. 4 bar abs.		HND-PS06**
0...2000 mbar abs.		10 mbar	max. 10 bar abs.		HND-PS07**
0...7.00 bar abs.		0.1 mbar	max. 1.4 bar		External threads G 1/4, stainless steel 
0...350.0 mbar rel.	1 mbar	max. 4 bar abs.	HND-PS09		
0...1000 mbar abs.		max. 14 bar abs.	HND-PS10		
0...3500 mbar abs.		max. 14 bar rel.	HND-PS11		
0...3500 mbar rel.		max. 28 bar abs.	HND-PS12		
0...7000 mbar abs.	10 mbar	max. 140 bar abs.	HND-PS13		
0...35.00 bar abs.		0.1 bar	max. 280 bar abs.	HND-PS14	
0...70.00 bar abs.			max. 600 bar abs.	HND-PS15	
0...160.0 bar abs.				HND-PS16	
0...250.0 bar abs.			HND-PS17		
0...400.0 bar abs.		HND-PS18			

* in the range from 0 to +50 °C

** Pressure sensors HND-PS01 up to HND-PS08 are only suitable for air and non corrosive/non ionising gases and liquids.



- Integrated pressure sensor
- 2 hose connections
- Differential pressure measurement
- Serial interface
- Extensive additional functions
- Relative pressure sensors

Description

The highly precise KOBOLD hand-held pressure measuring devices HNDP121/P231...HND-P127 are measuring devices with integrated pressure sensors. They have two pressure measurement inputs on the top of the housing, which are connected to the measuring points by means of stable metal connections and plastic hoses that are available as accessories. Numerous measuring ranges in the overpressure and underpressure range are available for various measurement tasks, such as differential pressure measurement. In addition to pressure display, these first-rate, compact, universally applicable measuring units offer additional functions such as minimum/maximum value memory, a hold function, tare function, automatic self-shut-off, or zero point offset. The devices with an expanded spectrum of functions also have a logger function, a peak value memory, minimum/maximum alarm, an adjustable measuring cycle, and averaging.

Areas of application

- Chemical, pharmaceutical, food industry
- Machine and apparatus construction
- Piping and container construction

Regarding: Type-specific technical Data

The measuring ranges given in brackets correspond to the maximum possible measuring ranges when using Minus and Plus connection spigots. The spigots may not be stressed beyond the beginning or final value listed in the standard measuring range. This is true both for the overpressure and the underpressure range. The measuring range reverses depending upon the use of the connection spigots.

Example HND-P121/-P231:

Maximum measuring range minus spigot

-25.00...+1.00 mbar;

Maximum measuring range plus spigot

-1.00...+25.00 mbar

Type-specific technical Data

HND-P121/-P231

Measuring range: -1.00 to 25.00 mbar
(-25.00...+25.00 mbar)

Accuracy: ±0.3% F.S.
(Hysteresis and linearity)
±0.4% F.S.
(in the range of 0 -50 °C)

Resolution: 0.01 mbar

Units: mbar, bar, Pa, kPa, mmHg, PSI, m
(switchable)

Overload: max. 10000 Pa (max. 100 mbar)

HND-P123/-P233

Measuring range: -10.0 to 350.0 mbar
(-350.0...+350.0 mbar)

Accuracy: ±0.2% F.S.
(Hysteresis and linearity)
±0.4% F.S.
(in the range of 0 -50 °C)

Resolution: 0.1 mbar

Units: mbar, bar, kPa, MPa, PSI, mmHg, m
(switchable)

Overload: max. 1 bar

HND-P126/-P236

Measuring range: -100 to 2000 mbar
(-2000...+2000 mbar)

Accuracy: ±0.2% F.S.
(Hysteresis and linearity)
±0.4% F.S.
(in the range of 0 -50 °C)

Resolution: 1 mbar

Units: mbar, bar, kPa, MPa, PSI, mmHg, m
(switchable)

Overload: max. 4 bar

HND-P127

Measuring range: -10.0 to 420.0 mbar
(-420.0...+420.0 mbar)

Accuracy: ±0.1% F.S.
(Hysteresis and linearity)
±0.4% F.S.
(in the range of 0 -50 °C)

Resolution: 0.1 mbar

Units: mbar, bar, kPa, MPa, PSI, mmHg, m
(switchable)

Overload: max. 1 bar



General Technical Data

Measurement input: by means of two metal hose stems

Sensor: piezo-resistive relative pressure sensor, for air or non-corrosive and non-ionising gases and liquids, not for water!

Display: 2 x 4-digit LC-displays

Operating temp.: 0 to +50 °C

Storage temp.: -20 to +70 °C

Storage humidity: 0 to 95 % r.H. (non-condensing)

Output: serial interface (via 3-pin jack, transformer on RS232 or USB optional)

Power supply: 9 V-monobloc battery (included in the scope of delivery), extern 10.5 - 12 V_{DC} via jack

Current consumpt.: < 1 mA (HND-P121...), max. 3 mA (HND-P231...)

Material: housing made of impact-resistant ABS plastic

Degree of protect.: IP 65, front

Dimensions: 142 x 71 x 26 mm (H x W x D)

Weight: approx. 160 g

Scope of functions:

Minimum/maximum value memory

Hold function: »freezing« of the current value

Automatic-off function: 1...120 min (can be deactivated)

Zero point adjustment via keyboard possible

Tare function: display, minimum/maximum values are set to zero

Battery change notification

Additional functions with

HND-P231, HND-P233, HND-P236:

Minimum/maximum alarm can be deactivated

Alarm (3 alarm settings)

Off: Alarm function inactive

On: Alarm notification via display, internal horn and serial interface

No Sound: Alarm notification only via display and interface

Averaging

Peak value memory unfiltered pressure peaks ≥ 10 msec

Adjustable measuring cycle:

»slow« 4 measurements/sec

»fast« ≥ 100 measurements/ sec (filtered)

»peak-detect« ≥ 100 measurements/sec

Power saving mode for measuring cycle »slow«

Real-time clock: current time

Logger functions:

Manual: 99 datasets

Cyclic: 9999 datasets

Adjustable cycle time: 1 sec...1 h

Order Data

Order-no.	Housing design
HND-P 121	2 measuring inputs, standard
HND-P 231	2 measuring inputs with additional functions (see techn. data)
HND-P 123	2 measuring inputs, standard
HND-P 233	2 measuring inputs with additional functions (see techn. data)
HND-P 126	2 measuring inputs, standard
HND-P 236	2 measuring inputs with additional functions (see techn. data)
HND-P 127	2 measuring inputs, greater sensor accuracy, standard

Connection material, see accessories on page 42



- Integrated pressure sensor
- 1 hose connection
- Serial interface
- Absolute pressure sensor
- Logger function with HND-P239

Description

The KOBOLD hand-held pressure measuring devices HND-P129 and HND-P239 have an integrated pressure sensor for absolute pressure measurement. The measuring device is connected to the measuring point by means of a stable, metal connection on the top of the housing and an optional plastic hose. This device design offers the possibility of also displaying the barometric air pressure in relation to sea level »zero«. In this case, air pressure is corrected by entering the height above »zero« in meters. Naturally, these devices also have the minimum/maximum value memory, a hold function, a tare function, automatic self-shut-off function, and zero point adjustment. The KOBOLD HND-P239 devices also offer additional functions like the logger function, peak value memory, minimum/maximum alarm, an adjustable measuring cycle, and averaging.

Areas of application

- Chemical, pharmaceutical, food industry
- Machine and apparatus construction
- Piping and container construction

Technical Data

Measuring range: 0 to 1300 mbar abs.
 Accuracy: ±0.2% F.S.
 (Hysteresis and linearity)
 ±0.4% F.S.
 (in the range of 0 - 50 °C)
 Resolution: 1 mbar
 Units: mbar, bar, kPa, MPa, mmHg, PSI, m
 (switchable)
 Overload: max. 4 bar absolute
 Measuring input: by means of a metal-hose stem
 Sensor: piezo-resistive absolute pressure sensor, for air or for non-corrosive and non-ionizing gases and liquids, not for water!
 Display: 2 x 4- digit LC-displays
 Operating temp.: 0 to +50 °C
 Storage temperature: -20 to +70 °C
 Storage humidity: 0 to 95% r.H. (non-condensing)

Technical Data (continued)

Output: serial interface
 (via 3-pin jack, transformer on RS232 or USB optional)
 Power supply: 9 V-monobloc battery
 (included in the scope of delivery), external 10.5 - 12 V_{DC} via jack
 Current consumption: < 1 mA (HND-P129), max. 3 mA (HND-P239)
 Material: housing made of impact-resistant ABS plastic
 Degree of protection: IP 65, front
 Dimensions: 142 x 71 x 26 mm (H x W x D)
 Weight: approx. 160 g

Scope of functions:

Minimum/maximum value memory
Hold function: »freezing« of the current value
Automatic-off function: 1...120 min (can be deactivated)
Zero point adjustment via keyboard possible
Tare function:
 Display, minimum/maximum values are set to zero

Battery change notification

Additional functions with HND-P239:

Minimum/maximum alarm can be deactivated
Alarm (3 alarm settings)
 Off: Alarm function inactive
 On: Alarm notification via display, internal horn and serial interface
 No Sound: Alarm notification only via display and interface

Averaging

Peak value memory unfiltered pressure peaks ≥10 msec

Adjustable measuring cycle:

»slow« 4 measurements/sec
 »fast« ≥ 100 measurements/sec (filtered)
 »peak-detect« ≥ 100 measurements/sec

Power saving mode in the measuring cycle »slow«

Real-time clock: current time

Logger functions:

Manual: 99 datasets
 Cyclic: 9999 datasets
 Adjustable cycle time: 1 sec...1 h

Order Data

Order-no.	Housing design
HND-P 129	1x pressure sensor input, standard
HND-P 239	1x pressure sensor input with additional functions (see techn. data)

Connection material, see accessories on page 42



Accessories for hand-held pressure measuring devices HND-P and sensor HND-PS

Order-no.	Description
HND-Z002	Plug power supply unit (220/240 V, 50/60 Hz), 10.5 V/10 mA
HND-Z011	Equipment protective housing bag, nappa leather, with 1 cut-out for round sensor connection
HND-Z012	Equipment protective housing bag, nappa leather, with 2 cut-outs for round sensor connection
HND-Z021*	Case with recess (275 x 229 x 83 mm)
HND-Z022*	Universal case with egg crate foam (275 x 229 x 83 mm)
HND-Z023*	Large case with recess (394 x 294 x 106 mm)
HND-Z031	Interface converter on RS232, galvanically isolated
HND-Z032	Interface converter on USB, galvanically isolated
HND-Z033	Adapter RS232 converter on USB- interface
HND-Z034	Windows software for setting and data read- and print-out of instruments of the HND-series with logger function
HND-Z081	Double nozzle for hose $\frac{9}{4}$ on hose $\frac{6}{4}$
HND-Z082	Hose clamp for hose $\frac{6}{4}$
HND-Z083	Adapter made of brass for G $\frac{1}{4}$ internal threads on hose $\frac{6}{4}$
HND-Z084	PVC-hose (5 bar), 6 mm external / 4 mm internal
HND-Z085	PE-hose (10 bar), 6 mm external / 4 mm internal
HND-Z086	PU-hose (9 bar), 6 mm external / 4 mm internal
HND-Z087	PA-hose (25 bar), 6 mm external / 4 mm internal

Additional accessories on request

*Observe instrument dimensions